DN ADSL VPN Firew	all Router
General Settings	; /
Firewall Security	
Security	🖉 Enable 🔿 Disable
	C All blocked/User-defined
Delieu	C High security level
Folicy	Medium security level
	C Low security level
(1) If some application (TCP:443,outbound allow	s cannot work after enabling Firewall, please check the Packet Filter especially Port Filter rules. For example, addi wed) will let HTTPS data go through Firewall.)
Block WAN Request	Enable C Disable
(ALEnable for preventi	ing any ping test from Internet, such as hacker attack.)
ASH	

ADSL VPN Firewall Router

Block WAN Request

Apply

BILLION ...

Configuration

LAN

WAN

Virtual Server

Save Config to FLASH

Language

General Settings				
Firewall Security				
Security	🕶 Enable 🔿 Disable			
Policy	C All blocked/User-defined			
	C High security level			
	Medium security level			
	C Low security level			
(If some applications cannot	work after enabling Firewall, please check the Packet Filter especially Port Filter rules. For ex			

(TCP:443, outbound allowed) will let HTTPS data go through Firewall.)

€ Enable ⊂ Disable

(
 Enable for preventing any ping test from Internet, such as hacker attack.)



4. Click on the 'OK' button.

X

ADSL VPN Firewall Router

Quick Start Configuration LAN WAN System Firewall ← General Setting Packet Fitter Intrusion Detect URL Filter IM/P2P Blockin Firewall Log

Virtual Server Time Schedule

Language

Save Config to FLASH

BILLION ...

Packet Filter

Add TCP/UDP Filter 🜔

Add Raw IP Filter 🕥

Dide Name	True Oshadada	Source IP / Netmask	Destand	Source port(s)	Inbound	
6. Click on 'Firewall'.		estination IP / Netmask	Protocol	Destination port(s)	Outbound	
	Abusus On	0.0.0.0 / 0.0.0.0	Tata	0 ~ 65535	Block	
mei_nttp Always On		<u> </u>	8. Click	8. Click on 'Add Raw IP Filter'.		
[7. Click on 'Packet Filter'.		0.0.0 / 0.0.0.0		0 ~ 65535	Block	
mer_uns Aiwa	Always On	0.0.0.0 / 0.0.0.0	UDP	53 ~ 53	Allow	
mei_tdns	Always On	0.0.0.0 / 0.0.0.0	TCP	0 ~ 65535	Block	
		0.0.0.0 / 0.0.0.0		53 ~ 53	Allow	
mei_ftp	Always On	0.0.0.0 / 0.0.0.0	TCP	0 ~ 65535	Block	
		0.0.0.0 / 0.0.0.0		21 ~ 21	Allow	
mei_tnet	Always On	0.0.0.0 / 0.0.0.0	ТСР	0 ~ 65535	Block	
		0.0.0.0 / 0.0.0.0		23 ~ 23	Allow	
mei_smtp	Always On	0.0.0.0 / 0.0.0.0	TCP	0 ~ 65535	Block	
		0.0.0.0 / 0.0.0.0		25 ~ 25	Allow	
mei_pop3	Always On	0.0.0.0 / 0.0.0.0	TCP	0 ~ 65535	Block	
		0.0.0.0 / 0.0.0.0		110 ~ 110	Allow	



· · · · · · · · · · · · · · · · · · ·
Status
Quick Start
Configuration
LAN
WAN
System
Firewall
General Settings
Packet Filter
Intrusion Detection
URL Filter
IM/P2P Blocking
Firewall Log
VPN
QoS
Virtual Server
Time Schedule
Advanced
Save Config to FLASH

BILLION TH

ADSL VPN Firewall Router

Packet Filter	
Add Raw IP Filter	
Rule Name Helper 💽	GRE
Time Schedule	Always On 💌
Protocol Number	47
Inbound	Allow -
Outbound	Allow 💌
Apply Return 오	

10. Click on the 'Apply' button.

BILLION ...

ADSL VPN Firewall Router

