

Wireless Security Set Up Instruction

Never use a wireless connected PC to configure the Router, otherwise you might experience a wireless disconnection then subsequently led to the settings cannot be apply properly. Please do use an Ethernet (RJ45) cabled to establish a wired connection in between your PC and the Router, before you attempt to configure the wireless security settings.

The screenshot displays the web interface of a Billion VoIP/802.11g ADSL2+ Firewall Router. The interface features a left sidebar with navigation options: Status, Quick Start, Configuration, LAN, Bridge Interface, Ethernet, IP Alias, Ethernet Client Filter, Wireless, Wireless Security, Wireless Client Filter, Port Setting, and DHCP Server. The 'LAN' menu item is highlighted in blue. The main content area shows the 'Wireless Security' configuration page. The 'Parameters' section includes a 'Security Mode' dropdown menu set to 'Disable'. Below the dropdown are 'Apply' and 'Cancel' buttons. A red arrow points from the 'LAN' menu item to the 'Wireless Security' configuration page. Another red arrow points from the 'Wireless Security' menu item to the 'Wireless Security' configuration page.

1. Click on 'LAN'.

2 Click on 'Wireless Security'.

Status

Quick Start

Configuration

LAN

Bridge Interface

Ethernet

IP Alias

Ethernet Client Filter

Wireless

Wireless Security**Parameters**

Security Mode	WPA1 Pre-Shared Key	3. Select mode from the dropdown list.
WPA Algorithms	TKIP	
WPA Shared Key	12345678	4. Enter the WPA password.
Group Key Renewal	3600	seconds
Idle Timeout	3600	seconds (120~65535)

Apply

Cancel

5. Click on the 'Apply' button.

Status

Quick Start

Configuration

LAN

Bridge Interface

Ethernet

IP Alias

Ethernet Client Filter

Wireless

Wireless Security

Wireless Client Filter

Port Setting

DHCP Server

WAN

System

Firewall

VoIP

QoS

Virtual Server

Time Schedule

Save Config to FLASH**Please confirm that you wish to save the configuration.***There will be a delay while saving as configuration information is written to FLASH chips.*

Apply

6. Click on the 'Apply' button.**7. Click on the 'Save Config' button.**

SAVE CONFIG

RESTART

LOGOUT



8. Click on the 'Save Config' button to complete the process.