

7800N Enabling WDS

Advanced 1

- Basic
- Status
- Quick Start
- Configuration 2**
 - LAN
 - Ethernet
 - IP Alias
 - IPv6 Autoconfig
 - Wireless 3**
 - Wireless Security
 - WPS
 - DHCP Server
 - WAN
 - System
 - Firewall
 - QoS

Configuration

Wireless

Parameters

WLAN Service	☒ Enable ☐ Disable
Time Schedule	1. Always On 2. TimeSlot1
Mode	802.11b + g + n
ESSID	7800n_lab
Hide ESSID	☐ Enable ☒ Disable
Regulation Domain	Europe
Channel ID	Channel 1 (2.412 GHz) 4
Channel Width	20/40MHZ
Tx Power Level	100 (0 ~ 100)
AP MAC Address	00:04ED:12:13:14
AP Firmware Version	2.2.0.3
WPS Service	☐ Enable ☒ Disable
WPS State	☐ Configured ☒ Unconfigured
WMM	☐ Enable ☒ Disable
Wireless Multicast Forwarding	☐ Enable ☒ Disable
Wireless Multicast Rate	30 Mbps

Wireless Distribution System (WDS)

WDS Service	☒ Enable ☐ Disable
Peer WDS MAC address	5 6 1. 00:60:33:b1:bb:af 2. 3. 4.

7 [Security settings](#)

Write down this Mac address, then enter it to the 2073N WDS Mac address list.

Enter 2073N's Mac address to this box.

Basic

- Advanced
- Status
- Quick Start
- WAN
- WLAN

Configuration

▼ Save Config to FLASH

Write settings to FLASH

9

8